


## Ordering Information

# Flexcon Extra-Flexible Steel Conduit

### Description

AFC Cable Systems, Inc. FLEXCON EXTRA-FLEXIBLE STEEL CONDUIT is manufactured from one continuous length of high grade steel, hot dipped in a zinc bath for protection against the normal effects of corrosion. The steel strip is formed into interlocking convolutions firmly joined to assure a rugged yet very flexible conduit which provides exceptional flexibility for tight U-bend applications. The convolutions are manufactured to insure smoother interior and exterior surfaces, which facilitate both cable and conduit pulling. The FlexCon installs easily with standard armored cable or flexible metal conduit connectors. The product is designed to be used for specific applications where Underwriters Laboratories Inc. or other agency approvals are not required.



### Ordering Information

### Product Dimensions/ Bend Radius

Product Code	Trade Size (inches)	Trade Size (mm)	Coil Length (feet)	Reel Length (feet)	Approx. Weight/100 feet (pounds)	Internal Diameter (min/max) inches	External Diameter (min/max) inches	Bend Radius (inches)
5101-24-00	3/8	12	50'	—	11.8	0.375/0.400	0.520/0.540	1.250
5101-30-00	3/8	12	—	100'	11.8	0.375/0.400	0.520/0.540	1.250
5101-42-00	3/8	12	—	250'	11.8	0.375/0.400	0.520/0.540	1.250
5102-24-00	1/2	16	50'	—	14.3	0.500/0.525	0.640/0.665	1.750
5102-30-00	1/2	16	—	100'	14.3	0.500/0.525	0.640/0.665	1.750
5103-24-00	3/4	21	50'	—	19.9	0.750/0.775	0.890/0.915	2.000
5103-30-00	3/4	21	—	100'	19.9	0.750/0.775	0.890/0.915	2.000

NOTE: All dimensions and weights are subject to normal manufacturing tolerances.